


# INMP32N

Industrial LED  
Right Angle Torch



## Description

- Widely used for inspection, emergency repair and construction emergency lighting etc. in industrial area and professional industry.
- The body is made of high performance nylon. It features as lightweight, anti-aging, anti-corrosion, impact-resistant and easy to carry.
- Professional optical lens design, soft illumination, uniform spot, in line with GB 30734 fire protection standard.



## Parameters

Certification:	CE
Working ambient temp.:	-40°C≤Ta≤+55°C
Ingress protection:	IP66/67
Corrosion-proof grade:	WF2
Rated voltage:	3×1.5V
CCT:	6500K
Luminous flux:	≥200lm (strong mode), ≥100lm (work mode), ≥100lm (SOS mode)
Run time:	≥9h (strong mode), ≥11h (work mode)
Beam distance:	≥85m (strong mode), ≥48m (work mode)
Battery type:	3×LR6AA (IEC60086)
Lifespan:	50,000h (without battery)

## Features



## Order specifications

Illustration	Luminous flux	Run time	Weight (g)	Order No.
	Strong mode: $\geq 200\text{lm}$ Work mode: $\geq 100\text{lm}$ SOS mode: $\geq 100\text{lm}$	Strong mode: $\geq 9\text{h}$ Work mode: $\geq 11\text{h}$	220	INMP32N

## Spare parts

Illustration	Description	Weight (g)	Order No.
Alkaline battery 	1.5V (IEC60086)	24	LR6AA

## Outline dimension (unit: mm)

